

EASY POWER XL E



PTC Easy Power XL **Electric Driven**

Easy Power XL E: unique flexibility for a multitude of applications.

General features:

- Sturdy painted tubular frame with anti-corrosion treatment
- Ergonomic grips for easier maneuverability
- AISI 304 stainless-steel coated panels
- Practical housings for gun and lance
- 2 x ø 400 solid wheels with steel axle and ball bearings + 2 castor wheels with brake
- Asynchronous three-phase 40 HP high-efficiency IE3 motor
- Flexible motor-pump coupling joint
- Industrial low-voltage (24V) power and control panel with star-delta starter and 30 feet of power cable
- Safety switch with thermal magnetic relay for motor protection
- Main switch, start/stop buttons, emergency stop
- Hour meter





EASY POWER XL E

Recommended Accessories

High pressure gun with lance (3.9 ft)	High pressure «Dump» gun with lance (3.2 ft)	Fan shape nozzle (15°-25°)	65.6 ft high pressure hose with S/S quick couplings	65.6 ft high pressure hose

Other Optional Accessories

Round jet nozzle 0°	Rotary nozzle	Foot valve complete with pipe flushing probe and reaction nozzle	Sand-blasting nozzle	Quick couplings on pump, delivery hose and gun	65.6 ft delivery hose extension kit with quick couplings	65.6 ft delivery hose extension kit	Stainless steel hose reel kit with 65.6 ft 3/8" rubber hose	Protection clothing TST	Hot water mobile generator

Unit Models

MODELS	FLOW RATE		PRESSURE	
	USgpm	l/min	psi	bar
EASYPOWER XL 400 E	10.0	38	5,800	400
EASYPOWER XL 500 E	8.0	30	7,250	500
EASYPOWER XL 800 E	5.0	20	11,600	800
EASYPOWER XL 1000 E	4.0	15	15,000	1000

Specifications subject to change without notice. All pumps and also the complete unit are tested prior to shipment. Customer training at our factory is available. PTC Waterblasting Systems can custom configure pump units to meet your specific requirements.



P.T.C. Waterblasting, LLC
 1601 Highway 13 East, Suite 100, Burnsville, MN 55337
 Ph. 320-340-6481 | www.ptcwaterblasting.com